

. AG

AFIRM GROUP

Apparel and Footwear International RSL Management Group **PACKAGING RESTRICTED SUBSTANCES LIST** Version 08 2025

Table of Contents

AFIRM Mission 3 AFIRM Vision 3 Legal Statement 3 Policy Statement 3
Scope of the AFIRM Packaging RSL4
Uses of the AFIRM Packaging RSL
Additional Substances and Parameters to Consider7
AFIRM Chemical Information Sheets9Definition of "Limit"9Definition of "Reporting Limits"9Definition of "Component"9
Change Log for the 2025 AFIRM Packaging RSL 10
Materials in Which Restricted Substances Are Likely to Be Found 11
AFIRM Packaging RSL
Appendix A. Per- and Polyfluorinated Chemicals

Apparel and Footwear International RSL Management (AFIRM) Group is the author of this work.

You may reuse or adapt this work, with or without attribution to AFIRM Group.







For more information about AFIRM, visit www.afirm-group.com.





AFIRM Mission & Vision

Mission

AFIRM Group (Apparel and Footwear International RSL Management Working Group, established in 2004) is on a mission to reduce the use and impact of harmful substances in the apparel and footwear supply chains.

Our purpose is to provide a forum to advance the global management of restricted substances in apparel and footwear, communicate information about chemicals management to the supply chain, discuss concerns, and exchange ideas for improving chemicals management.

Vision

AFIRM is recognized as a global center of excellence, providing resources to enable continuous advancement of chemicals management best practices.

We do this based on transparency, science, and collaboration with relevant industries and experts to build safer and more sustainable chemistry within the apparel and footwear supply chains.

As we implement this vision, AFIRM's mission, objectives, and projects will remain product-focused or RSL-related.

Legal Statement

The AFIRM Packaging RSL constitutes information from AFIRM only and does not represent any individual AFIRM member. Individual brand Packaging RSLs may differ in specific parameters.

The AFIRM Packaging RSL is not intended to and does not establish any industry standard of care. The AFIRM Packaging RSL may not always provide the most appropriate approach for any individual company's chemical management program. Many brands have implementation guidelines, and suppliers must follow those guidelines where required.

The AFIRM Packaging RSL does not constitute legal advice and is not a substitute for legal advice. There is no warranty, express or implied, as to the completeness or utility of the information contained in this AFIRM Packaging RSL, including, without limitation, that the information is current and error-free. AFIRM disclaims liability of any kind whatsoever resulting from any use of or reliance on the AFIRM Packaging RSL.

Policy Statement

AFIRM created this Packaging Restricted Substances List (AFIRM Packaging RSL) to assist and guide supply chain participants seeking to:

- Increase product quality and safety.
- Reduce their environmental impact by limiting the use of certain substances in packaging for apparel, footwear, accessories and related products including sporting good equipment, wearables, and home textiles.

Scope of the AFIRM Packaging RSL

The EU Packaging and Packaging Waste Directive defines packaging as:

All products made of any materials of any nature to be used for the containment, protection, handling, delivery, and presentation of goods, from raw materials to processed goods, from the producer to the user or the consumer. AFIRM acknowledges that the definition of packaging may vary by jurisdiction. For this reason, it is important to note the scope of product packaging coverage for the AFIRM Packaging RSL, outlined in Table 1. This scope ranges from product packaging (e.g. shoe boxes) to retail packaging (e.g. shopping bags). Suppliers are advised to consult AFIRM member brands on specific requirements for some packaging products. In addition, Table 2, on the next page, outlines examples of material types within the scope of the AFIRM Packaging RSL. Together, Tables 1 and 2 serve as a guide for brands and suppliers when identifying specific materials within each product packaging category.

Table 1. Examples of Products within the Scope of the AFIRM Packaging RSL

Hang Tags	Stickers	Protective Coverings	Trimmings	Sales Packaging	Transport Packaging
 Cords Foil stamps Hot stamp prints Paper hang tags Plastic hang tags Price tags Spot UV hang tags UPC tags 	 Antimicrobial stickers Labels, adhesive Price tags Tape 	 Lamination, matte or gloss Foam material Suit bags Plastic cases Poly bags Poly bags, zippered 	 Bead chain Collar bands Clips, metal Clips, plastic Eyelets/grommets Magnets Pins Tissue paper Zippers J-hooks Plastic fasteners 	 Boxes/cartons Gift boxes Retail carry bags Hangers (when sold with a clothing item) Spot UV boxes Suit bags Thermal receipt paper Tissue paper UV coated boxes Varnished coated boxes Water-based (aqueous) lacquer coated boxes 	 Antimicrobial stickers Boxes/cartons Corrugated shipping boxes/cartons J board Silica gel/desiccant sachets Stuffing materials, expanded foam materials Water-based (aqueous) lacquer-coated boxes

Scope of the AFIRM Packaging RSL

Table 2. Examples of Material Types within the Scope of the AFIRM Packaging RSL

Fibers			Coatings, Dyes & Prints	Natural Materials	Polymers, Plastics, Foams, Natural Bubber & Synthetic	Metal	Glue	Natural Leather	Synthetic Coated Fabric
Natural	Blended	Synthetic	FIIIItS		Rubber				
 Cotton Linen Silk Wool Lyocell (semi- synthetic) Rayon (semi- synthetic) Cellulose 	 Cotton- Polyester Ramie- Polyester Wool-Nylon 	 Acrylic Nylon Polyamide Polyester 	 Foil stamping Hot-stamp printing Spot UV Soft-touch coatings 	 Cork Paper Straw Stone Wood Cardboard Jacron (semi- synthetic paper product) 	 Acrylonitrile butadiene styrene (ABS) Ethylene vinyl acetate (EVA) Polystyrene (PS) Polyethylene (PE) Neoprene Polypropylene (PP) Polycarbonate (PC) Polyamide (PA) Polyurethane (PU) Polyurethane (PU) Polyvinyl chloride (PVC) Thermoplastic polyurethane (TPU) Thermoplastic elastomer (TPE) Styrene ethylene butylene styrene (SEBS) 	 Aluminum Brass Copper Stainless Steel 	 Contact adhesive Epoxies Powdered adhesive Flock adhesive Hot melt adhesive Latex glue Neoprene cement Polyurethane glue Silicone adhesive UV-cured adhesive 	• Leather • Fur & Hides	 Polyurethane (PU) Polyvinyl Chloride (PVC)



Uses of the AFIRM Packaging RSL

AFIRM member brands may differ on individual parameters; suppliers are advised to check with the customer regarding brand-specific requirements.

The AFIRM Packaging RSL should leverage AFIRM's mission — to reduce the use and impact of harmful substances in the apparel and footwear supply chain — by providing a single set of information for maximum and in-depth implementation within the supply chain.

Examples of uses for the AFIRM Packaging RSL, depending on the objectives of the user, include:

- Providing a tool for vendors to establish chemical management knowledge and processes.
- Building base compliance with AFIRM member chemical restrictions.
- Providing a common base for testing packaging, which may be accepted by multiple AFIRM brands.

AFIRM member companies determine and communicate to their vendors their testing requirements and acceptance of test reports.

Links and References

Be proactive! These links provide additional important information regarding chemical management and should be visited on a regular basis.

AFIRM Restricted Substances List

www.afirm-group.com/afirm-rsl

• Available in English, Simplified Chinese, Traditional Chinese, Vietnamese, Japanese, Indonesian, Spanish, and Turkish.

AFIRM Chemistry Toolkit

www.afirm-group.com/toolkit

• Available in English, Simplified Chinese, Traditional Chinese, Vietnamese, Japanese, Indonesian, Spanish, and Turkish.

AFIRM PFAS Phaseout Guidance

www.afirm-group.com/pfas-phaseout-guidance

 Available in English, Simplified Chinese, Traditional Chinese, Vietnamese, Japanese, Indonesian, Spanish, and Turkish.

AFIRM Explainer Videos

www.afirm-group.com/start-here

• Mostly available in English, Simplified Chinese, Vietnamese, Japanese, Indonesian, and Spanish, with additional translations forthcoming.

AFIRM Chemical Information Sheets

www.afirm-group.com/chemical-information-sheets

• Available in English, Simplified Chinese, Vietnamese, Japanese, Indonesian, and Spanish, with Traditional Chinese and Turkish translations forthcoming.

AFIRM Sampling Guidance

http://afirm-group.com/sampling-guidance

• Available in English

EU Packaging and Packaging Waste Regulation http://ec.europa.eu/environment/waste/packaging/ index_en.htm

Sustainable Packaging Coalition (SPC) www.sustainablepackaging.org Toxics in Packaging Clearinghouse (TPCH) https://toxicsinpackaging.org

Regulated fluorinated greenhouse gases; Regulation (EU) 2024/573 https://eur-lex.europa.eu/eli/reg/2024/573/oj

Regulated substances that deplete the ozone layer; Regulation (EU) 2024/590 https://eur-lex.europa.eu/eli/reg/2024/590/oj

Zero Discharge of Hazardous Chemicals (ZDHC) Foundation — Manufacturing Restricted Substances List (MRSL) https://mrsl.roadmaptozero.com

Additional Substances and Parameters to Consider

EU REACH Substances of Very High Concern

Based on scientific evidence indicating potential hazards to human health or the environment, the European Commission (EC) and European Union (EU) member states propose substances of very high concern (SVHCs) for placement on the European Chemicals Agency (ECHA) "Candidate List of Substances of Very High Concern for Authorisation."

Placing a substance on the Candidate List triggers specific obligations for importers, producers, and suppliers of any article that contains one or more of these substances above 0.1 percent by weight per component. The obligations include providing sufficient information to allow safe use of the article to brand and retail customers or, upon request, to a consumer within 45 days of receipt of the request.

In addition, ECHA must be notified if the substance(s) are present in article components above 0.1 percent in quantities totaling over one ton per producer or

importer per year. Notification is not required if the substance has already been registered for that use or when the producer or importer of an article can exclude exposure of humans and the environment during the use and disposal of the article. In such cases, the producer or importer must supply appropriate instructions to the recipient of the article.

ECHA periodically updates the Candidate List; find the most current version at www.echa.europa.eu/ candidate-list-table.

AFIRM member brands may differ on how they address SVHCs as well as the legal obligations. AFIRM advises suppliers to consult with their customers regarding brand-specific requirements for SVHCs.

California Proposition 65 Substances

Each year, California publishes a list of chemicals known to the state to cause cancer or reproductive toxicity.

Businesses that expose individuals to one or more of these chemicals above various thresholds must provide a clear and reasonable warning before the exposure occurs. For consumer products, this is typically through warning labels on the products or retail signage. Note that this warning is not the same as a regulatory requirement indicating that the product is "unsafe" if a specific concentration is exceeded. Enforcement is carried out through civil lawsuits brought by the California attorney general, district attorneys, or private parties acting in the public interest.

Additional information can be found at https://oehha. ca.gov/proposition-65.

AFIRM member brands may differ on how they address warning-label requirements. AFIRM advises suppliers to consult with their customers regarding brand-specific requirements for Proposition 65 substances.

Important: Compliance with AFIRM restricted substance limits does not prevent public or private parties from asserting that products violate Proposition 65 warning obligations.

Additional Substances and Parameters to Consider

Oxo-degradable Additives

The EU Commission on Waste and the Ellen MacArthur Foundation consider oxodegradable and oxo-biodegradable plastics to be problematic in current recycling/circular systems.

Manufacturers and users of these plastics should be aware that as of July 2021, the EU restricts placing oxo-degradable plastic on the market. Concurrently, several countries, including Saudi Arabia and the UAE, have legislation that requires plastics of certain grades to be oxo-degradable. These substances are subject to conflicting policies or legislation globally, and manufacturers should be aware and prepare accordingly.

Biocides, Nanoparticles, Sensitizers, Endocrine Disruptors, Etc.

Some brands may have specific requirements regarding the use of substances of concern such as biocides, nanoparticles, sensitizers, and endocrine disruptors.

AFIRM recommends checking with your customers regarding individual policies or requirements.

Bans on PVC Packaging

Countries around the world, including Canada, Spain, South Korea, and the Czech Republic, have banned or restricted PVC packaging.

AFIRM recommends that suppliers check with brand customers to understand whether they have a global PVC-free policy or, if not, if the products and packaging suppliers produce will be sold in these markets. Please note that this is an evolving space with additional markets potentially imposing this ban.

Additional and Upcoming Packaging Regulations

The EU Packaging and Packaging Waste Regulation gives provisions to member states on the essential requirements for packaging material (e.g. material composition).

However, member states can still implement additional rules. For example, France's anti-waste law, the Loi AGEC, bans the use of mineral oils in ink formulations for packaging prints. (See www. legifrance.gouv.fr/jorf/id/JORFTEXT000045733481.) The packaging regulatory space is evolving at a fast pace, with several jurisdictions working on new/updated requirements. AFIRM recommends checking with your customers for their own policies on packaging labelling.

AFIRM Chemical Information Sheets

AFIRM member brands have produced a comprehensive set of educational materials advising suppliers about best practices for chemicals management.

Each chemical information sheet covers a chemical or class of chemicals, giving an overview of the substance(s), where they are likely to be found in the material manufacturing process, and how to maintain compliance with the AFIRM RSL.

The sheets contain some information relevant to packaging, and future revisions will include more specific information.

The complete library of chemical information sheets is available on the AFIRM website at http://afirm-group.com/information-sheets: additionally, links to individual information sheets are embedded in the pages that follow.

The download icon next to a chemical or class of chemicals in the AFIRM RSL indicates that an information sheet is available.



Click on the icon or chemical name, and your web browser will open and download a PDF of the information sheet for that substance.

AG Chemical Information Shee Version 2.0 | March 2021

FORMALDEHYDE

CAS Number	Substance
Other Numer	Formalin, Methanal, Oxymethylene. Methylaldehyde, Oxomethane, Metl aldehyde, Methylene glycol, Methyl Formol, Carbonyl hydride

occurring naturally at low levels in foods and used in a
variety of synthetic preparations. At room temperature,
formaldehyde is a colorless, flammable gas that has a
distinct, pungent smell. Small amounts of formaldehyde
are naturally produced by plants, animals, and humans. ¹

aldehyde is a chemical with wides

Uses in the Supply Chain

Be Found In	Which of the (germanent press, easy care, measure); (fifting (crisk) (GS)), easi Resine or course, prelications using phenolic-, urse, measures, formaldelying and PT press, measures, formaldelying Professional Reck, and dickenge Professional Reck, and dickenge Heat transfer Adherive and glar septications including patching O. Obser control	Formaldehyde n paper, plywood, a preservative ir such as antisepti Formaldehyde c auxiliaries impa wrinkle free, dii characteristics tu Formaldehyde c for dyes and pig effects). It can a
	Castanta	adhesive and hes

may be used in the production of fertilizer, and urea-formaldehyde resins. It is also used as a some foods and in many house-hold products, ics, medicines, and cosmetics. an be used as one of the starting materials it rting textile performance features such as sional stability, and stain resistant mensional stability, and stain resistant o cotton and cotton blend fabrics. an be found in resins, binders, and fixing agents ments (especially those with fluorescent lso be used as a catalyst in certain printing, at transfer processes

Why Formaldehyde is Restricted

Legislation in major markets around the world restricts the presence of formaldehyde in finished products. Formaldehyde is classified as a probable human carcinogen and is an irritant which can affect the eyes, nose, and throat. In high concentrations formaldehyde can cause severe pain, gastrointestinal effects, vomiting, coma or de

Sourcing Compliant Materials from Your Suppliers

- Contact your suppliers and explain that you require materials to be compliant with the current AFIRM RSL limits.² Materials should have no intentionally added formaldehyde, in the processing or as residues for the following: Heat transfer Prints (such as flock and discharge)
 - Adhesives or glu
- Adhesives or glue
 Finishing agents
 Require suppliest to submit a confirmation of material compliance or a test report from a third-party labor.
 When materials are received, consider performing risk-based testing to ensure the current AFIRM RSL lim
- Check the Safety Data Sheets (SDS) of adhesives and glues to ensure formaldehyde is not listed as an ingredier

Definition of "Limit"

Some restrictions require that substance limits not be exceeded while others require that substance concentrations be below designated limits.

Test results should always be below designated restriction limits to ensure compliance with all requirements in all markets.

Definition of "Reporting Limits"

Values above which labs should report substances detected for purposes of data capture and harmonization.

By reporting these values, instead of a simple PASS/ FAIL, the supply chain can capture information regarding the presence of substances below Packaging RSL limits. The reporting limits also allow data to be harmonized between various testing labs.

Reporting limits are values at or above the method Practical Quantification Limit (PQL). The PQL represents the lowest level at which accurate, precise, and robust data can be reported. AFIRM Packaging RSL reporting limits are widely achievable by laboratories across the global analytical testing industry and allow for combined (composite) testing where applicable.

Definition of "Component"

A component is a part of packaging consisting of a material of uniform composition throughout. or a combination of materials that cannot be disioined or separated into different materials by abrasion, crushing, cutting, grinding, or unscrewing.

Components should be thought of as articles themselves for purposes of RSL compliance and are subject to each specified concentration limit. This includes the 0.1% threshold above which SVHCs may require disclosure under the EU REACH Regulation.

Change Log for the 2025 AFIRM Packaging RSL

CAS No.	Substance/Material	Modification	Page
Various	Azo-amines & Arylamine Salts	Updated test method for leather to EN ISO 17234-1:2024.	14
80-09-1	Bisphenol S (BPS)	Extended 1 ppm limit on BPA in receipt paper to cover BPS.	15
Various	Brominated and Organophosphorus Substances	 Renamed category from "Flame Retardants" to "Brominated and Organophosphorus Substances" since listed chemicals may have multiple uses. 	
115-86-6	Triphenyl Phosphate (TPP)	• Added Triphenyl Phosphate (TPP) with a 500 ppm limit due to placement on the REACH SVHC list.	16
3194-55-6	Hexabromocyclododecane (HBCDD)	• Reduced limit for HBCDD to 75 mg/kg pursuant to Regulation (EU) 2024/2555.	
Various	Fluorinated Greenhouse Gases	Changed legal reference to Regulation (EU) 2024/573.	6
Various	Ozone-depleting Substances	Changed legal reference to Regulation (EU) 2024/590.	6
Various	Organotins	 Updated Method CEN ISO/TS 16179:2012 to ISO 16179:2025 and removed method EN ISO 22744-1:2020. 	19
Various	Per- and Polyfluoroalkyl Substances (PFAS)	 Changed total organic fluorine limit to 50 ppm. Divided PFOS restriction into "PFOS and its salts" and "PFOS-related substances" with new limits. Included PFHxA and its salts and PFHxA-related substance restrictions. 	20, 22
53306-54-0	Phthalates - Bis(2-propylheptyl) phthalate (DPHP)	Added new orthophthalate DPHP with an information reporting requirement.	21

Materials in Which Restricted Substances Are Likely to Be Found

In the supply chain for apparel, footwear, and sporting equipment packaging, certain types of materials are more likely to contain restricted substances.

Brands may require packaging product or material testing prior to shipment to ensure that packaging articles comply with their Packaging RSLs; this information is included in brandspecific requirements.^A

AFIRM Group member brands agree on the chemicals included in the AFIRM Packaging RSL, the allowable limits, and the test methods. The responsibility for managing testing programs—the specific restricted chemicals that should be tested in specific materials and the frequency of such tests—remains with individual brands.

The AFIRM Packaging RSL Risk Matrix, shown in Table 3 on the next page, is presented as a guidance tool. It highlights the restricted substance risks associated with different fibers and materials. It is based on our many years of experience in manufacturing and in managing restricted substances across a wide range of materials.^B The aim is to provide information on those substances that have historically been deliberately used or found as reagent/contaminants in different materials.

It uses the following color code:

1 Red indicates that a chemical has been in widespread use and/or frequently detected in a particular material.

Orange indicates that a chemical has been deliberately used and/or detected in a particular material occasionally.

White indicates that we believe there is an almost negligible risk of a chemical being used and/or detected.

See footnotes for material-specific testing recommendations and exceptions.

In the absence of a brand Packaging RSL and testing program, the matrix outlined in Table 3 is a good starting point until you gain a true understanding of the risks within your specific supply chain. Use of this matrix should be accompanied by due diligence across all chemistries of concern.

The unified approach of the AFIRM Packaging RSL enables member brands to share test data more easily. We anticipate that the risk matrix will evolve to reflect realistic risks at any given time, which can then translate to testing options. Individual brand testing programs, to the extent they are different, supersede this guidance tool.

Determining Test Methods Using the AFIRM Packaging RSL Risk Matrix

The test methods listed in the Packaging RSL for specific materials correspond to the AFIRM Packaging RSL Risk Matrix.

A blank color code for any material will not have a corresponding test method.

For example, Metal has a blank color code for APEOs and therefore no test method is listed for APEOs for Metal in the RSL. If the RSL states "All Materials" or "All Materials Except," this means the test method is applicable to all materials listed with a color of 1 or 2 that do not have a specific test method listed.

AFIRM recommends consulting your testing laboratory to determine the best test method for any material not currently listed in this document.

A. See Section 5 of the AFIRM Chemistry Toolkit for more information on testing and Appendix B of the AFIRM Chemistry Toolkit for a model testing program if your customer does not have one of its own.

B. If a substance is a component of a combined material (for example, a laminated component like polymer material + cardboard), we recommend testing according to different material types.

Materials in Which Restricted Substances Are Likely to Be Found

Table 3. AFIRM Packaging RSL Risk Matrix

NOTE: This matrix provides representative examples of materials within each category but is not all-inclusive.

Substance		Fibers		Coatings, Dyes &	Natural Materials	Polymers, Plastics, Foams, Natural	Metal	Glue	Natural Leather	Synthetic Coated Fabric
		Blended	Synthetic	Prints	Including paper and cardboard	Rubber & Synthetic Rubber				
Alkylphenol (AP) and Alkylphenol Ethoxylates (APEOs), including all isomers	1	1	1	1	1	1A		1	1	1
Azo-amines and Arylamine Salts	1B	1B	1B		1B				1B	1B
Bisphenols		1	1	10	1D	2E			1	1
Brominated & Organophosphorus Substances						2F				
Butylhydroxytoluene (BHT)						2G				
Dimethylfumarate (DMFu)						2H			2	
Formaldehyde	2	2	2	1	1	2J		1	2	2
Heavy Metals, Total Content (Cd, CrVI, Pb, Hg) ¹				2	1K	2L	2		2	
Organotin Compounds				1		1		1	2	1
Per- and Polyfluoroalkyl Substances (PFAS)						Prohibited				
Phthalates				1M		1N		1	2P	1

 Please note that Chromium VI, Cadmium, Lead, and Mercury are restricted to a sum total of 100 ppm in several jurisdictions. Cadmium, Lead, and Mercury are analyzed using the same method even if the risk of finding them varies across different materials.

- A Level 1 for foams only; Level 2 for all other materials.
- B Level 1 for dyed/colored materials (non-white) only.

C Level 1 for PVC only; Level 2 for all other materials.

D Level 1 for thermal receipt and recycled paper only; Level 2 for all other materials.

E Level 2 for tapes, polycarbonate, and recycled plastic cases only; no testing requirement for other materials.

F Level 2 for materials with recycled content or if TPP use suspected in PU, TPU, or other polymeric materials.

- **G** Level 2 for poly bags only; no testing requirement for other materials.
- ${\rm H}$ Level 2 for silica gel packets and foam packaging only; ${\rm \ L}$ no testing requirement for other materials.
- J Level 2 for rubber only, no testing requirement for other materials.
- **K** Level 2 for materials with recycled content only; no testing requirement for other materials.
- L Level 2 for PVC only, no testing requirement for other materials.
- Level 1 for plastisol prints; Level 2 for all other materials.
- **N** Level 2 for polycarbonate and ABS, Level 1 for all other polymers.
- **P** Level 2 for patent or coated leather; no testing requirement for other materials.

CAS No.	Substance	Limits Component Materials	Potential Uses & Additional Information Processing for Packaging Materials	Suitable Test Method Sample Preparation & Measurement	Reporting Limit Limits Above Which Test Results Should Be Reported
	Alkylphenols (APs) Alkylphenol Ethoxylates (AP	EOs) including	all isomers		
Various	Nonylphenol (NP), mixed isomers	- Total: 100 ppm	APEOS are used as surfactants in the production of plastics, elastomers, paper, and textiles. These chemicals can be found in many processes involving foaming, emulsification, solubilization, or	Textiles and Leather: EN ISO 21084:2019 Polymers and all other materials:	Sum of NP & OP:
Various	Octylphenol (OP), mixed isomers		dispersion. APEOs can be used in paper pulping, lubrication oils, and plastic polymer stabilization. APs are used as intermediaries in	1 g sample/20 mL THF, sonication for 60 minutes at 70°C, analysis according to EN ISO 21084:2019	3 ppm
			the manufacture of APEOs and antioxidants used to protect or		
Various	Nonylphenol ethoxylates (NPEOs)		stabilize polymers. Biodegradation of APEOs into APs is the main source of APs in the environment.		
			APEOs and formulations containing APEOs are prohibited from use throughout supply chain and	All materials except Leather:	
Various	Octylphenol ethoxylates (OPEOs)	Total: 100 ppm	manufacturing processes. We acknowledge that residual or trace concentrations of APEOs may still be found at levels exceeding 100 ppm and that more time is necessary for the supply chain to phase them out completely. Recycled materials: Contact your brand customer for information about potential exemptions from the limit on NPEOs in recycled materials.	EN ISO 18254-1:2016 with determination of APEO using LC/MS or LC/MS/MS Leather: Sample prep and analysis using EN ISO 18218-1:2023 with quantification according to EN ISO 18254-1:2016	Sum of NPEO & OPEO: 20 ppm

CAS No.	Substance	Limits Component Materials	Potential Uses & Additional Information Processing for Packaging Materials	Suitable Test Method Sample Preparation & Measurement	Reporting Limit Limits Above Which Test Results Should Be Reported
	Azo-amines and Arylamine Salts				
92-67-1	4-Aminobiphenyl				
92-87-5	Benzidine				
95-69-2	4-Chloro-o-toluidine				
91-59-8	2-Naphthylamine				
97-56-3	o-Aminoazotoluene				
99-55-8	2-Amino-4-nitrotoluene				
106-47-8	p-Chloraniline				
615-05-4	2,4-Diaminoanisole		Azo dyes and pigments are colorants that incorporate one or several azo groups (-N=N-) bound with aromatic compounds. Thousands of azo dyes exist, but		
101-77-9	4,4'-Diaminodiphenylmethane				
91-94-1	3,3'-Dichlorobenzidine				
119-90-4	3,3'-Dimethoxybenzidine			All materials except leather: EN ISO 14362-1:2017 Leather: EN ISO 17234-1:2024 p-Aminoazobenzene:	
119-93-7	3,3'-Dimethylbenzidine				
838-88-0	3,3'-dimethyl-4,4'-Diaminodiphenylmethane				
120-71-8	p-Cresidine	20 ppm each			5 ppm each
101-14-4	4,4'-Methylen-bis(2-chloraniline)	20 ppm each	the listed cleavable amines are		
101-80-4	4,4'-Oxydianiline		restricted.	All materials except leather:	
139-65-1	4,4'-Thiodianiline		are regulated and should no longer	Leather: EN ISO 17234-2:2011	
95-53-4	o-Toluidine		be used for dyeing textiles.		
95-80-7	2,4-Toluenediamine				
137-17-7	2,4,5-Trimethylaniline				
95-68-1	2,4 Xylidine				
87-62-7	2,6 Xylidine	-			
90-04-0	2-Methoxyaniline (= o-Anisidine)				
60-09-3	p-Aminoazobenzene				
3165-93-3	4-Chloro-o-toluidinium chloride				
553-00-4	2-Naphthylammoniumacetate				
39156-41-7	4-Methoxy-m-phenylene diammonium sulphate				
21436-97-5	2,4,5-Trimethylaniline hydrochloride				

CAS No.	Substance	Limits Component Materials	Potential Uses & Additional Information Processing for Packaging Materials	Suitable Test Method Sample Preparation & Measurement	Reporting Limit Limits Above Which Test Results Should Be Reported
	Bisphenols				,
80-05-7	Bisphenol-A (BPA)		BPA may be used in the production of epoxy resins, polycarbonate plastics, flame retardants, and PVC. BPS may be used as a substitute for BPA for some specific uses, including in thermal receipt paper.		
80-09-1	Bisphenol-S (BPS)	Receipt paper: BPA and BPS: 1 ppm Other packaging: 1000 ppm each In preparation for forthcoming restrictions, significantly lower levels of bisphenols should be achievable, e.g., in polyamide, over time or better alternatives should be substituted if possible.	BPS and BPF can be found in polyamide dye-fixing agents and in sulfone- and phenol- based leather synthetic tanning agents. BPA and BPS: ppm BPA and BPS can be found in recycled polymeric and paper materials due to polycarbonate plastic and thermal receipt paper	 Leather: EN ISO 11936:2023 All other materials: Extraction: 1 g sample/20 ml THF, sonication for 60 minutes at 60°C, analysis with LC/MS Note for textiles: For precipitation, draw the extract to another container and add methanol or acetonitrile. This keeps the extraction process consistent. 	Leather: 10 ppm each All other materials: 0.1 ppm for individual samples 1 ppm for composite samples
77-40-7	Bisphenol-B (BPB)		made with bisphenols entering waste streams. BPA, BPS, and BPB are included on the REACH SVHC list. Additional restrictions on the entire class of bisphenols are expected, with a revised restriction proposal		
620-92-8	Bisphenol-F (BPF)		Important: Compliance with bisphenol (and other) limits in the AFIRM Packaging RSL does not prevent public or private enforcers from asserting that packaging violates California Proposition 65 warning obligations. AFIRM recommends testing relevant materials for bisphenols according to the Testing Matrix and to work with suppliers to minimize residual concentrations or replace them with better alternatives where possible.		

CAS No.	Substance	Limits Component Materials	Potential Uses & Additional Information Processing for Packaging Materials	Suitable Test Method Sample Preparation & Measurement	Reporting Limit Limits Above Which Test Results Should Be Reported				
	Brominated & Organophosphorus Substances								
1163-19-5	Decabromodiphenyl ether (DecaBDE)		Flame retardant substances, including the entire class of						
32534-81-9	Pentabromodiphenyl ether (PentaBDE)	Total: 500 ppm	organohalogen flame retardants, should no longer be applied to packaging materials during production. Listed here are relevant flame retardants included in the Stockholm Convention. These substances should not be used for any other purpose, e.g., as plasticizers or softeners. Impurities						
79-94-7	Tetrabromobisphenol A (TBBP A)			All materials: EN ISO 17881-1:2016	5 ppm each				
40088-47-9	Tetrabromodiphenyl ether								
36483-60-0	Hexabromodiphenyl ether		_	found may come from electronic waste recycling streams, e.g., polystyrene, and can impede future recycling opportunities. The EU is seeking to reduce limits on polybrominated diphenyl ethers (PBDEs) to improve material					
68928-80-3	Heptabromodiphenyl ether				The EU is seeking to reduce limits on polybrominated diphenyl ethers (PBDEs) to improve material				
3194-55-6	Hexabromocyclododecane (HBCDD)	75 ppm	recyclability. Once adopted, new limits will be included.						
115-86-6	Triphenyl phosphate (TPP)	500 ppm	May be used as a flame retardant, an antioxidant for PU materials, or as an alternative plasticizer to orthophthalates. Now included on the REACH SVHC list.	All materials: EN ISO 17881-2:2016	50 ppm				
	Butylated Hydroxytoluene (BHT)								
128-37-0	Dibutylhydroxytoluene (BHT)	25 ppm	Used as an additive in plastics as an antioxidant to prevent aging. Can cause phenolic yellowing of textiles.	All materials: ASTM D4275:2017	5 ppm				

CAS No.	Substance	Limits Component Materials	Potential Uses & Additional Information Processing for Packaging Materials	Suitable Test Method Sample Preparation & Measurement	Reporting Limit Limits Above Which Test Results Should Be Reported
	Dimethylfumarate				
624-49-7	Dimethylfumarate (DMFu)	0.1 ppm	DMFu is an anti-mold agent used in sachets in packaging to prevent the buildup of mold, especially during shipping.	All materials: ISO 16186:2021	0.05 ppm
	Formaldehyde				
50-00-0	Formaldehyde	150 ppm	Formaldehyde can be found in polymeric resins, binders, and fixing agents for dyes and pigments, including those with fluorescent effects. It is also used as a catalyst in certain printing, adhesives, and heat transfers. Formaldehyde can be used in antimicrobial applications for odor control. Formaldehyde found in packaging can off-gas directly onto product. Composite wood materials (e.g., particle board and plywood) must comply with California and U.S. formaldehyde emission requirements (40 CFR 770). Though formaldehyde legislation does not specifically apply to packaging, suppliers are advised to refer to brand-specific requirements for these materials.	Wood: EN 717-3:1996 Paper: DIN EN 645:1994 & EN 1541:2001 Textiles, Finishings, Dyes, Inks & Coatings: JIS L 1041-2011 A (Japan Law 112) or EN ISO 14184-1:2011 Leather: EN ISO 17226-2:2019 with EN ISO 17226-1:2021 confirmation method in case of interferences. Alternatively, EN ISO 17226-1:2021 can be used on its own.	16 ppm

CAS No.	Substance	Limits Component Materials	Potential Uses & Additional Information Processing for Packaging Materials	Suitable Test Method Sample Preparation & Measurement	Reporting Limit Limits Above Which Test Results Should Be Reported
	Heavy Metals (Total Content)				
7440-43-9	Cadmium (Cd)	Total: 100 ppm	Cadmium compounds are used as pigments (especially in red, orange, yellow and green) and in paints. It can also be used as a stabilizer for PVC.	All materials: Total heavy metals (Cd, Cr, Pb & Hg): DIN EN 16711-1: 2016 If the total of four heavy metals exceeds 100 ppm and Cr contributes to the sum, test for Cr VI. This test method detects metal elements (Cd, Cr, Hg, Pb). When the final value >100 ppm and Cr contributes to the sum, the Cr VI method described below should be used to exclude the presence of Cr VI. Metal: IEC 62321-7-1:2017 The testing laboratory will convert the test result into ppm. Natural leather and natural materials: EN ISO 17075-1:2017 and EN ISO 17075-2:2017 for confirmation in case the extract causes interference. Alternatively, EN ISO 17075-2:2017 may be used on its own. All other materials: IEC 62321-7-2:2015	5 ppm
7439-92-1	Lead (Pb)		May be associated with plastics, paints, inks, pigments, and surface coatings.		10 ppm
7439-97-6	Mercury (Hg)		Mercury compounds can be present in pesticides and as contaminants in caustic soda (NaOH). They may also be used in paints.		5 ppm
18540-29-9	Chromium VI		Though typically associated with leather tanning, Chromium VI also may be used in pigments, chrome plating of metals, and wood preservatives.		3 ppm

CAS No.	Substance	Limits Component Materials	Potential Uses & Additional Information Processing for Packaging Materials	Suitable Test Method Sample Preparation & Measurement	Reporting Limit Limits Above Which Test Results Should Be Reported
	Organotin Compounds				
Various	TributyItin (TBT)	0.5 ppm coch			
Various	Triphenyltin (TPhT)	- 0.5 ppm each			
Various	Dibutyltin (DBT)				
Various	Dioctyltin (DOT)		Class of chemicals combining tin and organics such as butyl and phenyl groups. Organotins are predominantly found in the environment as antifoulants in marine paints, but they can also be used as biocides (e.g., antibacterials), catalysts in plastic and glue production, and heat stabilizers in plastics/rubber. In textiles and apparel packaging, organotins are associated with plastics/rubber, inks, paints, metallic glitter, polyurethane products and heat transfer material. AFIRM recommends restricting "Other Organotins" as a matter of best practice consistent with other industry restricted substances lists.	All materials: ISO 16179:2025	0.1 ppm each
Various	Monobutyltin (MBT)				
Various	Monooctyltin (MOT)	1 ppm each			
Various	Tricyclohexyltin (TCyHT)				
Various	Trimethyltin (TMT)				
Various	Trioctyttin (TOT)				
Various	Tripropyltin (TPT)				
Various	Dimethyltin (DMT)	Other Organotins: 1 ppm each			
Various	Diphenyltin (DPhT)				
Various	Dipropyltin (DPT)				
Various	Monomethyltin (MMT)				
Various	Monophenyltin (MPhT)				
1461-25-2	Tetrabutyltin (TeBT)				
597-64-8	Tetraethyltin (TeET)				
3590-84-9	Tetraoctyltin (TeOT)]			

CAS No.	Substance	Limits Component Materials	Potential Uses & Additional Information Processing for Packaging Materials	Suitable Test Method Sample Preparation & Measurement	Reporting Limit Limits Above Which Test Results Should Be Reported
	Per- and Polyfluoroalkyl Substances (PFAS)				
Various	All PFAS as measured by total organic fluorine	50 ppm	Regulations around the world ban the use of PFAS in packaging. PEAS may be used in commercial	EN 14582:2016 or ASTM D7359:2023 or EN 17813:2023 Methods quantify total fluorine (inorganic + organic). See AFIRM PFAS Phaseout Guidance for additional information about total versus total organic fluorine.	20 ppm for individual sample 50 ppm for max. composite of two samples
Various	Perfluorooctane sulfonate (PFOS) and its salts	25 ppb total	 PFAS may be used in commercial water-, oil-, and stain-repellent agents as well as in breathable membranes that remove moisture, e.g., PTFE. Refer to Appendix A for a list of PFAS substances and CAS Numbers for which testing can be conducted to indicate whether PFAS chemistry is present above restricted levels due to intended use or unintended contamination. See AFIRM PFAS Phaseout Guidance for a recommended testing approach to ensure compliance with all global regulations using the methods included in this section. Recycled packaging: Contact your brand customer about potential exemptions from the limit on total organic fluorine in recycled textile products. 	 And stain-repellent ts as well as in breathable branes that remove moisture, PTFE. r to Appendix A for a list FAS substances and CAS bers for which testing can onducted to indicate whether Schemistry is present above cted levels due to intended use intended contamination. AFIRM PFAS Phaseout ance for a recommended gapproach to ensure bliance with all global ations using the methods ded in this section. rcled packaging: Contact your d customer about potential nptions from the limit on total nic fluorine in recycled textile ucts. 	25 ppb total
Various	PFOS-related substances	1000 ppb total			1000 ppb total
Various	Perfluorooctanoic Acid (PFOA) and its salts	25 ppb total			25 ppb total
Various	PFOA-related substances	1000 ppb total			1000 ppb total
Various	Perfluorohexane-1-sulphonic acid (PFHxS) and its salts	25 ppb total			25 ppb total
Various	PFHxS-related substances	1000 ppb total			1000 ppb total
Various	C9-C14 Perfluorocarboxylic acids (PFCAs) and their salts	25 ppb total			25 ppb total
Various	C9-C14 PFCA-related substances	260 ppb total			260 ppb total
Various	PFHxA and its salts	25 ppb total			25 ppb total
Various	PFHxA-related substances	1000 ppb total			1000 ppb total

CAS No.	Substance	Limits Component Materials	Potential Uses & Additional Information Processing for Packaging Materials	Suitable Test Method Sample Preparation & Measurement	Reporting Limit Limits Above Which Test Results Should Be Reported
	Phthalates				
28553-12-0	Di-Iso-nonylphthalate (DINP)				
117-84-0	Di-n-octylphthalate (DNOP)				
117-81-7	Di(2-ethylhexyl)-phthalate (DEHP)				
26761-40-0	Diisodecylphthalate (DIDP)				
85-68-7	Butylbenzylphthalate (BBP)				50 ppm each
84-74-2	Dibutylphthalate (DBP)		Estors of orthol phthalic acid		
84-69-5	Diisobutylphthalate (DIBP)		Esters of ortno-phthalic acid (Phthalates) are a class of organic compound commonly added to plastics to increase flexibility. They are sometimes used to facilitate the		
84-75-3	Di-n-hexylphthalate (DnHP)				
84-66-2	Diethylphthalate (DEP)				
131-11-3	Dimethylphthalate (DMP)		moulding of plastic by decreasing its		
131-18-0	Di-n-pentyl phthalate (DPENP)		 melting temperature. Phthalates can be found in: Flexible plastic packaging Components (e.g., PVC) Plasticol print pastes Adhesives Plastic sleeves Polymeric coatings The REACH substances of very high concern (SVHC) candidate list is updated frequently. Suppliers should assume that the AFIRM Packaging RSL includes all Phthalates on the SVHC list — whether itemized here or not. 	All materials: CPSC-CH-C1001-09.4, analysis by GC/MS	
84-61-7	Dicyclohexyl phthalate (DCHP)				
71888-89-6	1,2-Benzenedicarboxylic acid, di-C6-8-branched alkyl esters, C7-rich	500 ppm each Total: 1000 ppm			
117-82-8	Bis(2-methoxyethyl) phthalate				
605-50-5	Diisopentyl phthalate (DIPP)				
131-16-8	Dipropyl phthalate (DPRP)				
27554-26-3	Diisooctyl phthalate (DIOP)				
68515-50-4	1,2-Benzenedicarboxylic acid, dihexyl ester, branched and linear				
71850-09-4	Diisohexyl phthalate (DIHxP)				
68515-42-4	1,2-Benzenedicarboxylic acid, di-C7-11-branched and linear alkyl esters (DHNUP)	-			
84777-06-0	1,2-Benzenedicarboxylic acid Dipentyl ester, branched and linear				
68648-93-1	1,2-Benzenedicarboxylic acid, di-C6-10-alkyl esters or mixed decyl and hexyl and octyl diesters with ≥ 0.3% of dihexyl phthalate; 1,2-Benzenedicarboxylic acid, mixed				
68515-51-5	decyl and hexyl and octyl diesters; 1,2-Benzenedicarboxylic acid, di-C6-10-alkyl esters				
776297-69-9	n-Pentyl-isopentylphthalate (nPIPP)				
26040-51-7	Bis(2-ethylhexyl) tetrabromophthalate				
53306-54-0	Bis(2-propylheptyl) phthalate (DPHP)	For informational purposes only. AFIRM recommends testing to assess content levels.			

Appendix A. Per- and Polyfluoroalkyl Substances (PFAS)

NOTE: This list is a subset of PFAS and is not exhaustive. Findings would indicate intentional use or significant contamination.

CAS No.	PFAS Name	CAS No.	PFAS Name
	PFOS and Its Salts		PFHxS and Its Salts, continued
251099-16-8	Didecyldimethyl ammonium perfluorooctane sulfonate (PFOS-N(C10H21)2(CH3)2)	55120-77-9	Perfluorohexane Sulfonic acid, lithium salt (PFHxS-Li)
1763-23-1	Perfluorooctanesulfonic acid (PFOS)	68259-08-5	Perfluorohexane Sulfonic acid, ammonium salt (PFHxS-NH4)
2795-39-3	Perfluorooctanesulfonic acid, potassium salt (PFOS-K)	82382-12-5	Perfluorohexane Sulfonic acid, sodium salt (PFHxS-Na)
29457-72-5	Perfluorooctanesulfonic acid, lithium salt (PFOS-Li)		PFHxS-related Substances
29081-56-9	Perfluorooctanesulfonic acid, ammonium salt (PFOS-NH $_4$)	68259-15-4	N-Methylperfluoro-1-hexanesulfonamide (N-Me-FHxSA)
70225-14-8	Perfluorooctane sulfonate diethanolamine salt (PFOS-NH(OH) $_{2}$)	41997-13-1	Perfluorohexane sulfonamide (PFHxSA)
56773-42-3	Perfluorooctanesulfonic acid, tetraethylammonium salt (PFOS-N($C_2H_{s),a}$)		C9 – C14 PFCAs and Their Salts
	PFOS-related Substances	375-95-1	Perfluorononanoic Acid (PFNA, C9-PFCA)
4151-50-2	N-Ethylperfluoro-1-octanesulfonamide (N-Et-FOSA)	335-76-2	Perfluorodecanoic Acid (PFDA, C10-PFCA)
31506-32-8	N-Methylperfluoro-1-octanesulfonamide (N-Me-FOSA)	2058-94-8	Perfluoroundecanoic Acid (PFUnA, C11-PFCA)
1691-99-2	2-(N-Ethylperfluoro-1-octanesulfonamido)-ethanol (N-Et-FOSE)	307-55-1	Perfluorododecanoic Acid (PFDoA, C12-PFCA)
24448-09-7	2-(N-Methylperfluoro-1-octanesulfonamido)-ethanol (N-Me-FOSE)	72629-94-8	Perfluorotridecanoic Acid (PFTrDA, C13-PFCA)
307-35-7	Perfluoro-1-octanesulfonyl fluoride (POSF)	376-06-7	Perfluorotetradecanoic Acid (PFTeDA, C14-PFCA)
754-91-6	Perfluorooctane sulfonamide (PFOSA)	172155-07-6	Perfluoro-3-7-dimethyloctanecarboxylate (PF-3,7-DMOA)
	PFOA and Its Salts		C9 – C14 PECA-related Substances
335-67-1	Perfluorooctanoic acid (PFOA)	17741-60-5	1H 1H 2H 2H-Perfluorododecyl actylate (10·2 FTA)
335-95-5	Sodium perfluorooctanoate (PFOA-Na)	2144-54-9	1H 1H 2H 2H-Perfluorododecyl methaciylate (10:2 FTMA)
2395-00-8	Potassium perfluorooctanoate (PFOA-K)	865-86-1	1H 1H 2H 2H-Perfluorododecanol (10:2 FTOH)
335-93-3	Silver perfluorooctanoate (PFOA-Ag)	34598-33-9	2H 2H 3H 3H-Perufloroundecanoic acid (H4PELInA)
335-66-0	Perfluorooctanoyl fluoride (PFOA-F)	678-39-7	Perfluorooctylethanol 8:2 (8:2 ETOH)
3825-26-1	Ammonium pentadecafluorooctanoate (APFO)	39239-77-5	1H 1H 2H 2H-perfluorotetradecap-1-ol (12:2 FTOH)
	PFOA-related Substances	120226-60-0	1H 1H 2H 2H-Perfluorododecanesulphonic acid (10:2 FTS)
39108-34-4	1H,1H,2H,2H-Perfluorodecanesulfonic acid (8:2 FTS)	2043-54-1	1H 1H 2H 2H-Perfluorododecul iodide (10:2 FTI)
376-27-2	Methyl perfluorooctanoate (Me-PFOA)	30046-31-2	1H 1H 2H 2H-Perfluorotetradecyl iodide (12:2 FTI)
3108-24-5	Ethyl perfluorooctanoate (Et-PFOA)	00040 01 2	
678-39-7	2-Perfluorooctylethanol (8:2 FTOH)	007.04.4	
27905-45-9	1H,1H,2H,2H-Perfluorodecyl acrylate (8:2 FTA)	307-24-4	Pertiuorohexanoic Acid (PFHxA, C6-PFCA)
1996-88-9	1H,1H,2H,2H-Perfluorodecyl methacrylate (8:2 FTMA)		PFHxA-related Substances
27854-31-5	2H,2H-Perfluorodecanoic acid (H2PFDA)	17527-29-6	1H,1H,2H,2H-Perfluorooctyl acrylate (6:2 FTA)
	PFHxS and Its Salts	2144-53-8	1H,1H,2H,2H-Perfluorooctyl methacrylate (6:2 FTMA)
355-46-4	Perfluorohexane Sulfonic acid (PFHxS)	27619-97-2	1H,1H,2H,2H-Perfluorooctanesulfonic acid (6:2 FTS)
3871-99-6	Perfluorohexane Sulfonic acid, potassium salt (PFHxS-K)	647-42-7	1H,1H,2H,2H-Perfluorooctanol (6:2 FTOH)

AFIRM Packaging Restricted Substances List | 2025



www.afirm-group.com